

製 品		粒度	孔眼寸法	規格値		目標値					塩酸可溶鉄量保証 値 (Fe <sub>2</sub> O <sub>3</sub> %)
A-37	A-S		残留率								
	○	8-5 mm	micron %	+8000 10 max	-4750 10 max	8000/6700 10-25	6700/5600 25-45	5600/4750 30-50			0.010 max
	○	5-3 mm	micron %	+4750 15 max	-2800 5 max.	4750/4000 25-45	4000/3350 35-55	3350/2800 10-25			0.010 max
	○	3-1 mm	micron %	+2800 10 max	-1000 10 max	2800/1700 45-65	1700/1000 35-50				0.010 max
	○	-1 mm	micron %	+1000 5 max.	-250 30 max	1000/500 40-60	500/250 20-40				0.020 max
○		2-3 mesh	micron %	+9500 10 max	-5600 10 max	9500/8000 25-45	8000/6700 30-50	6700/5600 10-35			0.010 max
○	○	3-6 mesh	micron %	+6700 2 max.	-3350 10 max	6700/4750 35-50	4750/4000 20-35	4000/3350 20-35			0.010 max
		3-8 mesh	micron %	+6700 5 max.	-2360 10 max	6700/5600 5-20	5600/4000 20-40	4000/2800 25-50	2800/2360 10-25		0.010 max
○	○	6-14 mesh	micron %	+3350 5 max.	-1000 5 max.	3350/2800 10-20	2800/2360 15-25	2360/1400 45-55	1400/1000 10-20		0.010 max
		8-14 mesh	micron %	+2360 5 max.	-1180 5 max.	2360/2000 25-40	2000/1700 20-35	1700/1180 25-40			0.010 max
○	○	14-28 mesh	micron %	+1400 0	-500 3 max	1400/1000 15-25	1000/710 55-65	710/500 15-25			0.010 max
○	○	28-48 mesh	micron %	+710 1 max.	-300 37:10max. S:15max	710/600 5-15	600/425 45-70	425/300 15-40			0.010 max
	○	-6 mesh	micron %	+3350 5 max.	-500 5-20	3350/2360 20-35	2360/1700 15-30	1700/1000 15-30	1000/500 10-20		0.015 max
	○	-8 mesh	micron %	+2360 5 max.	-600 10-35	2360/1180 40-60	1180/600 20-35				0.015 max
○	○	-14 mesh	micron %	+1180 5 max.	-300 10-35	1180/600 40-60	600/300 15-30				0.020 max
○	○	-28 mesh	micron %	+710 1 max.	-106 30 max	710/500 5-15	500/300 30-45	300/180 15-25	180/106 5-15		0.020 max
		-48 mesh(Type II)	micron %	+500 0	-106 25 max	500/300 15-35	300/180 30-45	180/106 15-30			0.020 max
○	○	-48 mesh(Type I)	micron %	+300 5 max	-45 60 max	300/180 15-25	180/106 10-20	106/45 15-25			0.050 max
○	○	-60 mesh	micron %	+250 5 max	-45 60 max	250/180 5-15	180/106 15-25	106/45 25-40			0.050 max
○	○	-100 mesh	micron %	+150 5 max	-45 50 min.	150/75 10-25	75/45 10-25				0.050 max
○	○	-325 mesh	micron %	+45 5 max		-20 55-75					0.050 max
○		-10 μm	micron %	+10 10 max		-1 10-30					0.050 max

※○印以外は特別注文になります。